

## TECHNICAL DATA

| PROPERTY              | METHOD        | <b>PALISADE SA-HT</b><br>TYPICAL VALUE   |
|-----------------------|---------------|--|
| Color                 | -             | <b>KOOL BLUE™</b>                        |
| Top Surface           | -             | <b>STRONGHOLD™</b> Anti-Skid: Polymer    |
| Bottom Release Liner  | -             | Silicone Split Release Poly              |
| Permeability          | ASTM E96-00   | 0.01 perms                               |
| Nominal Thickness     | ASTM D1777    | 40 mil (1 mm)                            |
| Nail Sealability      | ASTM D1970    | Pass                                     |
| Lap Sealability       | ASTM D1970    | Pass                                     |
| Tensile Strength      | ASTM D226     | 121 lbf/in. (21kN/m)                     |
| Tear Strength         | ASTM D4523    | 160 lbf/in. (28 kN/m)                    |
| Elongation            | ASTM D2523-00 | 16%                                      |
| Low Temperature Flex. | ASTM D1970    | -22° F (-30° C) - Pass                   |
| Adhesion to Plywood   | ASTM D1876    | 55 lbf/in.: 75° F (9.6 kN/m: 24° C)      |
| Adhesion to Plywood   | ASTM D1876    | 23 lbf/in.: 40° F (4 kN/m: 4.4° C)       |
| UV Exposure           | ASTM G90      | 6 months                                 |
| Temperature Range     | ASTM D1970    | LT: 15° F (-9° C) to HT: 250° F (121° C) |
| Dimensions            | -             | 36 in. x 66.7 ft. (91.4 cm x 20.3 m)     |
| Square/Roll           | -             | 2  |
| Roll Weight           | -             | 45 lbs. (21 kg)                          |
| Rolls/Pallet          | -             | 30                                       |

410-130 Bridgeland Avenue, Toronto, Ontario, Canada M6A-1Z4  
 Toll Free: 866-747-4035 • Fax: 866-840-3857 • [sdp-products.com](mailto:sdp-products.com)  
 eMail: [info@sdp-products.com](mailto:info@sdp-products.com)



# PALISADE™

# SA-HT

Self-Adhered, High Temperature (HT) Underlayment



## BUILD ON OUR STRENGTH™

## SDP ADVANCED POLYMER PRODUCTS



Patent Pending **Skid Resistant Technology** delivers superior walking and roof loading traction.



Unique **KOOL BLUE™** color technology produces lower heat absorption and lower glare.



Advanced **UV Technology** allows for up to **6 months** UV exposure before the final roof covering is applied.



**30 Year Limited Warranty.**  
Designed for long-life roof materials.

**HT 250**  
**HI-TEMP ADHESIVE**


Advanced **technology** adhesive formulation for superior **High Temperature Performance.**

**ASTM**  
**D-1970**

Designed to **exceed the toughest** industry code standards.



**PALISADE™ SA-HT**  
**SELF ADHERED UNDERLAYMENT**



**PALISADE™ SA-HT**  
**SELF ADHERED UNDERLAYMENT**